

A NEW RANGE OF COMPACT GENERATORS BY HIMOINSA

HCY COMPACT SERIES

6-12 KVA



3 MODELS

- Best in Class Power Train
- Large Fuel Tank Capacity
- Low Noise Level



3000 RPM

- 250 Hour Service Intervals
- High-quality Compact Design
- Low Fuel Consumption



KVA

6 & 9kVA (Single Phase)
12kVA (Three Phase)

PHASES

1

3

FREQUENCY

50
HZ

3000
RPM

STANDARD VOLTAGES

50
HZ

3

50
HZ

1

415/240V

240V

CONSTRUCTION • MINING • RESIDENTIAL • COMMERCIAL

HIMOINSA – A Yanmar Company & Leading Generator Manufacturer delivers superior quality generators ensuring a continuous efficient supply of energy. Himoinsa Generators are low maintenance providing endurance and durability.



GENERATOR POWER
A **YANMAR** COMPANY



HIMOINSA
A YANMAR COMPANY

HIMOINSA COMPACT SERIES STANDARD FEATURES:

1. FUEL ACCESIBILITY Fuel filling cap
2. FUEL CONTROL Fuel gauge on roof
3. HANDLING 2 Lifting points to ensure safe lifting and transport.
4. RADIATOR ACCESIBILITY External Access for radiator cooling filling.
5. BEST IN CLASS POWER TRAIN Yanmar engine and MeccAlte alternator.
6. SECURITY Battery isolator switch.
7. ACCESIBILITY / MAINTENANCE Removable door for easy maintenance. Lock with high hardness and tensile strength with key press lock.
8. SECURITY Emergency stop switch.
9. CONNECTIONS AND CONTROL
 - 3 Australian type sockets. IP66
 - RCBO Vigi breakers
 - Battery switch
 - Battery charger (Optional)
 - M7 Digital controller
 - Cubicle door with key locker
10. HANDLING Heavy duty forklift pockets.
11. PROTECTIONS Bunded tray 110% with drain access.
12. PROTECTIONS Air inlet rain Hood to prevent water ingress to the retention tray.

Easy Maintenance



Removable Door




Battery Isolator Switch



External Access



Heavy Duty Forklift Pockets



2 Lifting Points



Environmentally Friendly



Powered by
YANMAR



SERVICE INTERVAL

250 hours



		HCY6 M	HCY9 M5	HCY12 T5
Rated Output (COP)	kW / kVA	5,5	8	9 / 11,3
Max Output	kW / kVA	6	8,6	10 / 12,45
Voltage	V	240	240	415
Phase		1	1	3
Engine Speed	rpm	3000		
Engine Model		YANMAR - 3TNM68 HHFCG		
Alternator Model		MeccAlte ECP3 2S/2	MeccAlte ECP3 3S/2	MeccAlte ECP3 3S/2
FOC	l/h	3,8		
Service Interval	hours	250		
Weight	kg	430		
Dimensions (LxWxH)	mm	1529x775x928		
Noise Level	dB(A)	69		
Control System		M7		

Tank Capacity 39L

SYDNEY LOCATION:
69 – 73 Violet St,
Revesby NSW 2212
PHONE: 1300 767 257
FAX: +61 2 9772 3666

BRISBANE LOCATION:
28 Duntroon Street,
Brendale QLD 4500
PHONE: (07) 3186 5285
FAX: +61 2 9772 3666

CANBERRA:
4/80 Newcastle Street
Fyshwick ACT 2609
TEL: 1300 767 257



GENERATOR POWER
A YANMAR COMPANY